

W.A. HAMMOND DRIERITE COMPANY MANUFACTURERS
DRIERITE, "THE VERSATILE DESICCANT"
CONSULTING AND ENGINEERING SERVICE DRYING SOLIDS, LIQUIDS, GASES
MATERIAL SAFETY DATA SHEET
IDENTITY: INDICATING DRIERITE CONTENTS: CALCIUM SULFATE 97%, COBALT CHLORIDE 3%

SECTION I

MANUFACTURER'S NAME: W.A. HAMMOND DRIERITE COMPANY
ADDRESS: 138 DAYTON AVENUE, P.O. BOX 460, XENIA, OHIO 45385
EMERGENCY TELEPHONE: CHEMTREC 1-800-424-9300
TELEPHONE NUMBER FOR INFORMATION: 1-513-376-2927
DATE PREPARED : 5-9-86 REVIEWED : 7/12/89

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

HAZARDOUS COMPONENTS (CHEMICAL IDENTITY)	COMMON NAME	OSHA PEL (MG/M3)	ACGIH TLV (MG/M3)	C.A.S. NO.	%
COBALTOUS CHLORIDE (AS COBALT)	COBALT CHLORIDE	0.1	0.05*	1332-82-7	3

* RECOMMENDED

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT : N/A SPECIFIC GRAVITY (H2O=1): 1.87
VAPOR PRESSURE (MMHG): N/A MELTING POINT : N/A
VAPOR DENSITY (AIR=1): N/A EVAPORATION RATE
SOLUBILITY IN WATER : 0.3 G/100ML (BUTYL ACETATE=1) : N/A
APPEARANCE AND ODOR : BLUE GRANULES, NO ODOR

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (METHOD): N/A FLAMMABLE LIMITE: LEL N/A UEL N/A
EXTINGUISHING MEDIA: WATER
SPECIAL FIREFIGHTING PROCEDURES : N/A
UNUSUAL FIRE AND EXPLOSION HAZARDS: N/A

SECTION V - REACTIVITY DATA

STABILITY : STABLE; CONDITIONS TO AVOID: N/A
INCOMPATIBILITY (MATERIALS TO AVOID) : STRONG OXIDIZING AGENTS
HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: THERMAL DECOMPOSITION MAY
PRODUCE CHLORINE.
HAZARDOUS POLYMERIZATION : WILL NOT OCCUR
CONDITIONS TO AVOID : N/A

SECTION VI - HEALTH HAZARD DATA

ROUTE(S) OF ENTRY: INHALATION !X! SKIN !! INGESTION !!
CARCINOGENICITY: NTP: NO; IARC MONOGRAPHS: NO; OSHA REGULATED: NO
HEALTH HAZARDS (ACUTE & CHRONIC) / SIGNS AND SYMPTOMS OF EXPOSURE:
THIS PRODUCT CONTAINS 3% COBALT CHLORIDE WHICH CAUSES EYE IRRITATION AND
MAY CAUSE SKIN AND UPPER RESPIRATORY TRACT IRRITATION. OVEREXPOSURE TO
COBALT COMPOUNDS MAY CAUSE NOSE AND THROAT IRRITATION AND AN ALLERGIC SKIN
RASH. THEY ARE MILDLY IRRITATING TO THE EYES AND IF INGESTED, MAY CAUSE
VOMITING, DIARRHEA AND A SENSATION OF HOTNESS. EXCESSIVE INHALATION AND/OR
INGESTION OF COBALT SALTS MAY AFFECT THE KIDNEYS, LUNGS, AND THYROID.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

RESPIRATORY SYSTEM CONDITIONS AND SKIN DISEASES.

EMERGENCY AND FIRST AID PROCEDURES:

IF INHALED, REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRA
TION, PREFERABLY MOUTH-TO-MOUTH. IF BREATHING IS DIFFICULT, GIVE OXYGEN.
CALL A PHYSICIAN. IF SWALLOWED, GIVE TWO GLASSES OF WATER AND INDUCE
VOMITING IMMEDIATELY. CALL A PHYSICIAN. NEVER GIVE ANYTHING BY MOUTH TO AN
UNCONSCIOUS PERSON. IN CASE OF CONTACT, IMMEDIATELY FLUSH EYES WITH PLENTY
OF WATER FOR AT LEAST 15 MINUTES. CALL A PHYSICIAN.

DOC 3

PAGE 2

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

VENTILATE AREA OF SPILL. COLLECT MATERIAL INTO APPROPRIATE CONTAINERS FOR
REUSE OR DISPOSAL. MATERIAL MAY ALSO BE FLUSHED WITH WATER TO A WASTEWATER
TREATMENT SYSTEM.

WASTE DISPOSAL METHOD:

DISPOSE IN CLOSED CONTAINERS, AT AN APPROVED LANDFILL, IN ACCORDANCE WITH
LOCAL, STATE AND FEDERAL REGULATIONS. MATERIAL MAY ALSO BE FLUSHED WITH
WATER TO A WASTEWATER TREATMENT SYSTEM.